

WET WALL DETECTOR

Non-destructive MOISTURE DETECTOR for Exterior Insulation and Finish Systems

The detection, evaluation and accurate locating of excess moisture in substrate beneath exterior insulation finish systems can be difficult, costly and time consuming and can involve the inspector making a large number of holes in the EIFS. With this in mind, Tramex have developed a new, non-destructive, moisture meter, the **Wet Wall Detector**.

The **Wet Wall Detector** has been specially developed for the detection, location, and tracking of excess moisture within and behind EIFS.

This electronic instrument will read through fiber reinforced lamina and exterior insulation to locate and evaluate excess moisture that may be present in the sheathing substrate and wood stud.

The **Wet Wall Detector** is the latest, most practical and useful moisture meter you can have when conducting a moisture survey on buildings with EIFS claddings.



- **For non-destructive moisture evaluation of EIFS**
- **For tracing moisture back to source**
- **Fast and easy to operate**
- **Instant clear readings**
- **Light-weight hand-held and battery operated**
- **Inexpensive to purchase and operate**

The **Wet Wall Detector** is designed and manufactured by TRAMEX who have been producing a range of moisture measurement and detection instruments for construction and construction material since 1980.

The problems of excess moisture in EIF systems

By visual inspection the location of excess moisture and decay behind an EIF system of wall cladding can be difficult and near impossible as normal evidence of this moisture and decay are not visible on either side of the wall. Excess moisture can be hidden and trapped in the substrate and within the thickness of the wall. If these conditions are allowed to continue the moisture will increase as will the rot and decay, eventually leading to possible failure of the cladding system and the structure. Also wet insulation loses its thermal value resulting in unnecessary heat loss or gain and thermal movement in the structure. So in the interest of all concerned, early detection of these problems, or potential problems and corrective remedial action makes good economic sense.

How does the Wet Wall Detector work?

The Wet Wall Detector is an electronic hand-held moisture detector working on the principle of electronic impedance. With impedance measurement harmless signals are transmitted from the electrodes at the base of the instrument deep into the thickness of the wall. These signals measure the change in electronic impedance which is translated into a relative moisture content reading and instantly displayed on the clear large analog dial. Readings are instant and continuous. The Wet Wall Detector is also fitted with an audible device which sounds at high readings. The Wet Wall Detector will give vital information necessary to evaluate and carry out moisture assessment on the condition of most fiber reinforced EIFS and similar systems at an affordable cost without complications.

The fast non-destructive way to detect excess moisture


Tramex Wet Wall Detector has been specially developed to aid in the detection, location and tracing of excess moisture within the cladding, the sheathing and the wood stud on EIF systems. The Wet Wall Detector is non-destructive in operation which means that it can detect excess moisture without the need to mechanically probe, cut, or damage the surface. The Wet Wall Detector's low frequency electronic signal can read through the glass fiber reinforced lamina and insulation deep into the substrate. It is easy and fast to use, light to carry and can be operated with one hand. Having detected the excess moisture the Wet Wall Detector can be of great benefit in tracing this moisture back to its point of ingress or source.

Specification

- Dimensions:** 125mm x 275mm x 70mm
4.75" x 11" x 3"
- Weight:** 1.8kg (4lbs)
- Power supply:** One 9 volt battery
- Sensitivity:** Two ranges:
Low for 1" (25mm) systems
High for thicker systems
- Accessories:** Leather carrying case

Warranty

The Wet Wall Detector carries a full parts and labor warranty for a period of one year from the date of first purchase.



Tramex manufactures a range of moisture meters including: Probe-type Resistance Meters with a choice of electrodes. Non-destructive moisture meters for flooring, roofing, wood and building inspection.

Manufactured by

Tramex Limited, Station House, Shankill Business Centre, Shankill, Co. Dublin, Ireland. Tel: (353) 1-282 3688 or Fax: (353) 1-282 6311
USA: Tramex, C/o Black Hawk Sales Inc., 28 Pin Oak Drive, Littleton, CO80127. Tel: 303 972 7926. Fax: 303 972 7106

Distributor